

Specialty Chemicals P.O. Box 640 Orange, Texas 77631-0640

# Honeywe

Phone: (409

Fax: (409

**Assays** 

Fax:

Attention:

**QUALITY ASSURANCE** 

Order No:

SAMPLE

Grade:

ACUMIST(R) B-12

**Shipping Date:** 

ACPA Order No: SAMPLE

Item

PSM

PSM

Date of Manufacture

Mean

Тор

Lot - Sublot J1B122-001

01/21/2019

microns 10.9 microns

28.38

Minimum:

Maximum:

11.5

44.00

WHITE TO OFF-WHITE POWDER ESSENTIALLY FREE FROM FOREIGN MATTER

Thomas H Moyers Quality Assurance Leader

## **ACumist® B-12**

Micronized Polyethylene Homopolymer for use in solvent borne coatings, stains and lacquers, and solvent based flexographic inks. As with all ACumist products, it is insoluble in solvents and UV based monomers and oligomers at room temperature.

#### TYPICAL PROPERTIES

Property	Value
Hardness	<1.0
Drop Point, Mettler	126°C (259°F)
Density	0.96
Acid Number	Nil

#### REGULATORY APPROVALS

Property	Value
Plastic Pipe Institute/NSF*	No
FDA Indirect Approvals*	Yes

### PRODUCT FORM AND SIZE

Property	Value
Product Form	Micronized powder
Size	10.0 to 11.5

DISCLAIMER: Although all statements and information contained herein are believed to be accurate and reliable, they are presented without guarantee or warranty of any kind, express or implied. Information provided herein does not relieve the user from the responsibility of carrying out its own tests and experiments, and the user assumes all risks and liability for use of the information and results obtained. Statements or suggestions concerning the use of materials and processes are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that all toxicity data and safety measures are indicated herein or that other measures may not be required.

@ 2021 Honeywell International Inc.

All rights reserved

Honeywell

Specialty Products

Honeywell P. O. Box 640 Orange, TX 77631-0640

Phone (409) 886-7445 Fax (409) 882-3601

June 02, 2020

Dear Customer:

Subject: Shelf Life - A-C®, ACumist®, AClyn®, Honeywell Titan® and NduroMatt®, Cohesa® products

- The recommended shelf life of A-C®, ACumist®, Honeywell Titan® and NduroMatt® products is three (3) years.
- The recommended shelf life of AClyn® products is two (2) years.
- The recommended shelf life of Cohesa® is one (1) or two (2) years (depends on product and package type/size) if the product stored and handled in a specific temperature conditions between 5 and 33 degrees Celsius.

Should you have any questions, please do not hesitate to let me know.

Sincerely,

Chrisitne Craig Leader-Quality Assurance