

Qualleaps Europe, S.A.U. O Jola Grena, 49 28109 Alcohendas (Madrid): Españo / Spain Telefone: +34 - 91 663 78 00 Fax 434-91 663 88 30

CERTIFICATE OF ANALYSIS

This is to certify that the information below has been approved by QA as conforming to Qualicaps Europe specifications, as described in the current technical manual and applicable regulatory requirements

CUSTOMER:

OMFE, S.A.

ITEM DESCRIPTION: 4BZEBZE

CUSTOMER ITEM:

E00347F

LOT NUMBER:

E1207141

PRINTING:

LOT QUANTITY APPROVED: 1200000

INK COLOR:

NOT APPLICABLE NOT APPLICABLE **COUNTRY: SPAIN**

CUSTOMER ORDER:

PEDIDO JP0305

NAME:

APPROVAL DATE:

8/10/2012

MANUFACTURING DATE: 1/10/2012

EXPIRY DATE:

5 YEARS

GELATIN: Complies with the requirements of current EP and USP/NF editions.

It is of pure bovine origin, complies with revision in force of European Guideline EMEA/410/01. Each supplier has a Ph. Eur certificate of suitability for their product (R1-CEP-2000-027-Rev.02, R1-CEP-2000-029-Rev.04, R1-CEP-2002-110-Rev.00, R1-CEP-2001-211.Rev.01) and has confirmed that it is manufactured from raw material not imported from UK, Ireland and Portugal.

COLORANTS: Comply with the EC directives 2009/35 & 2008/128 and where applicable with the requirements of the European Pharmacopoeia and the FDA.

RINTING INKS: Comply with pharmaceutical regulations.

FINISHED PRODUCT TESTS

CAPSULES: Do not contain preservatives and have not been treated with Ethylene Oxide. They comply with The European Agency for the Evaluation of Medicinal Products (EMEA) guideline CPMP/ICH/283/95 and the European Pharmacopoeia for residual solvents. DISINTEGRATION: Less than 15 minutes by the Ph. Eur. test and have a rupture time of less than 5 minutes by the USA Federal Specification 285A Acid Solubility Test.

PARAMETERS	LIMITS	REFERENCE	RESULT
	MICROBIOLOGICAL	AND CHEMICAL TE	ST
Total Aerobic Microbial Count	(TAMC)10 ³ CFU/G	EP/USP	
Salmonella	Negative / 10 G	EP/USP	Meets test
	Negative / 1 G		
	Negative / 1 G,		
	Negative / 1 G		

DIAMETER	CAP (mm)	Meets spec	TM*	5,32	•	5,31	(max-min
	BODY (mm)		TM*	5,06	-	5,05	(max-min
LENGTH (CAP (mm)		TM*	7,4	**	7,1	(max-min
	BODY (mm)		TM*	12,5	•	12,3	(max-min
END THICKNESS	CAP (micr)	Meets spec	QS*	167	-	105	(max-min
		Meets spec	QS*	157		97	(max-min
WEIGHT (MG)		Meets spec	TM*	41	(Average)		
MOISTURE (%)		Meets spec	TM*	14,4	(Average)		



^{*}TM = Qualicaps Technical Manual
*QS = Qualicaps internal specification
"Meets test" means conforms to specification