

## Srikem Laboratories Pvt. Ltd.

Plot No. 17/24, M.I.D.C. Taloja, -410 208, Navi Mumbai. Tel.: 2741 0459, 2740 2408, 65108581, Fax: 91-22-2740 2631. E-mail:srikem@vsnl.com Website:www.srikem.com

## **CERTIFICATE OF ANALYSIS**

 Product
 : Permethrin (Pharma Grade) 99%
 COA No.
 : 0965/18

 Batch No.
 : 184046005
 Report No.
 : FP-288/18

 Mfg. Date
 : Sep.2018
 Mfg. Lic. No.
 : KD-324

 Exp. Date
 : Aug.2023
 Dispatch Qty.
 : 100 Kg

TEST	OBSERVATION	LIMIT
Characters	Yellow brownish colour liquid which	Yellow brownish colour liquid which
(Description & Solubility)	solidify on standing at lower temperature.	may solidify on standing or at lower temperature.
	Soluble in Alcohol (96 % W/V),	Soluble in Alcohol
	Acetone, Ether & Hydrocarbons	(96 % W/V) Acetone, Ether &
	(Toluene).	Hydrocarbons (Toluene).
Identification Infrared Absorption	A) By IR	A) By IR
	IR Spectrum exhibits maxima which are	IR Spectrum exhibits maxima which
	only at the same wave number as those in	are only at the same wave number as
	spectrum of Permethrin working	those in "Reference Spectrum of
	Standard.	Permethrin- Reference Standard".
	B)By HPLC	B)By HPLC
	Retention time of Permethrin test sample	Retention time of Permethrin test
	matches with retention time of Permethrin	sample matches with retention time of
	standard in the assay test.	Permethrin standard in the assay test.
Loss On Drying	0.21 %	Not more than 2.0 %
Related Substance By HPLC	Meta Phenoxy Benzyl Alcohol: 0.0974%	NMT 0.15 %
	Meta Phenoxy Benzyaldehyde: 0.0183%	NMT 0.15 %
	DV Acid Ester (Cis+Trans): BDL	NMT 0.15 %
	Unknown Impurity: 0.1698%	NMT 0.30 %
	Total Impurity: 1.0624 %	NMT 2.0 %
Sulphated Ash	0.03 %	Not more than 0.2 %
Assay by HPLC	99.05%	98.0% to 101.0%
(on dried basis)	1 172	
Cis Isomer	26.01%	23.0% to 27.0%
Residual Solvents	Toluene: 14.31 ppm	Not More Than 890 ppm
	*Benzene: BDL	Not More Than 2 ppm

Note: - Before sampling stir well & warm up to 40°C Permethrin solidifies below 35°C. In case of solidification please warm up to 40 to 45°C toget liquid (Before use). This does not affect the quality.

/		
Remarks : Passes As Per Specification		
*Benzene is not used in process, but tested due to the use of Toluene.		
Prepared By/Date:-	Approved By/Date:-	
threlal oct. 22,2018	Batil oct. 22,2018	
	oct. 22,200	
Mr. Uday Vetal (QA/RA Asst. Manager)	Mrs. Kanchan Patil (Asst. Manager QA)	

Head. Off.: #311, Bldg.No.6, Jogani Ind.Estate, Chunabhatti Mumbai-400 022. Tel.:+91-22-24055088 Fax+91-22-24055070/+91-22-24045896

Annexure No.: SQA/066/A01-00 SOP No.: SQA/O/066-00 Page 1 of 1